MATERIAL SAFETY DATA SHEET

IDENTIFICATION

Product Name: SANIFOAM

Trade Name: U.N. Number:

Other Names:

Manufacturers Code:

Dangerous Good Class/
& Subsidiary Risk:

Hazchem Code:

Poison Schedule:

Use: Sanitizing Cleaner

Physical Description/Properties

Appearance: Clear, pale yellow liquid

Boiling Point (°C) 100°C

Vapour Pressure (mm Hg@25°C) 24

Per Cent Volatiles: 83

Specific Gravity @ 20°C 1.09

Flash Point: Nil

Flammability Limits (%): Nil

Auto ignition Temperature (°C) Nil

Plus other properties if applicable

IngredientsProportionChemical Entity(High 60%)

Chemical Entity
(Include all (Medium 10% - 60%)
hazardous Ingredients)
(Low 10%)

hazardous Ingredients)Sodium Hydroxide
Sodium Hypochlorite

Surfactants/Foaming Boosters/Water

HEALTH HAZARD INFORMATION

Health Effects

Swallowed: Soreness and redness of mouth and throat. Nausea,

vomiting and stomach pain may occur

Eyes: Pain and redness. Corneal burns may occur.

Skin: Redness and irritation. Possible burns

Inhaled: Shortness of breath, coughing and sore throat

This information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Sanifoam Page 2 of 2

First Aid

Swallowed: DO NOT induce vomiting. Give two glasses of

water and obtain medical attention

Eyes: Immediately flush eye(s) with running water for

15 minutes and obtain medical attention.

Skin: Remove contaminated clothing and flush affected

area with water. Obtain medical attention if contact

is extensive or prolonged.

Inhaled: Unlikely route unless atomised. Move to fresh air and

obtain medical attention if shortness of breath develops.

PRECAUTIONS FOR USE

Advice to Doctor: Full details available from National Poison (03) 474-0999

Exposure Limits: Contains 3% max. Available chlorine

TLV TWA for chlorine: 0.5ppm

Ventilation: Poorly ventilated areas (e.g. tanks) may require self-

contained, positive pressure breathing apparatus.

Personal Protection: PVC/rubber gloves, splash goggles, gumboots.

Flammability: Not flammable. If involved in fire chlorine fumes will

be evolved.

SAFE HANDLING INFORMATION

Storage and Transport: Store in cool, dry area. Corrosive Class 8 and Toxic

Substances, 4th Schedule conditions apply

Spills and Disposal: Contain spill and absorb with inert material then

place in clean drums for disposal by approved

methods

Fire and Explosion Hazard: Will not support combustion but if involved in a

fire, decomposition may give off chlorine. Fire fighters may consider breathing equipment.

Contact Point: (09) 262-0800 Date: 18 December 2000

This information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.